



HOSE REELS FOR COMPRESSED AIR, SERIES EASY ROLLER



Art. no. 3610

Art. no. 3615

Art. no. 9400+3610
 Art. no. 9400+3615
 Art. no. 9408

Automatic rewind, spring-driven hose reel, with plastic enclosure (made of nylon and polypropylene) and pivoting wall bracket, suitable for the use with compressed air and water (temperature range: -10°C – +60°C) and for hoses of 8 x 12 mm (or 10 x 14 mm) with a max. length of 15 m (or 10 m).

Inlet connection air: 1/4" BSP.

Max working pressure: 20 bar.

The standard colour of the enclosure is red with yellow cover. Also available in blue with red cover, in dark grey or yellow (as images above).

Art. no. 9400+3610

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 8 x 12 mm and 10 m length. Standard connection threads 1/4" BSP.

Art. no. 9400+3615

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 8 x 12 mm and 15 m length. Standard connection threads 1/4" BSP.

Art. no. 9408

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 10 x 14 mm and 10 m length. Standard connection threads 3/8" BSP.



Art. no.	Hose length	Hose diameter	Connection threads	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9400+3610	10 m	8 x 12 mm	1/4" BSP (M)	20 bar	8.1 kg	220x310x380
9400+3615	15 m				8.2 kg	
9408	10 m	10 x 14 mm	3/8" BSP (M)			